DEVELON DX25Z-7 2.5T TRACKED EXCAVATOR

Details

Price:	POA
Dealer Stock #:	DX25Z-1
New / Used:	Dealer New



Seller Details

Name:	DWL Machinery
Phone:	(02) 8311 1321
Dealer License No:	8706626
State:	NSW
Suburb:	Austral
Postcode:	2179

Sales Representatives

Jacob

© 2015-2026 TruckDealers.com.au. All Rights Reserved.

Description

FOLLOW US FOR ALL NEW LISTINGS: @dwlmachinery Ph: Andrew 0401 873 538 or 1300 DIAL DWL _____ The DEVELON DX25Z-7 2.5T Tracked Excavator delivers exceptional power, precision, and reliability in a compact zero tail swing design. Ideal for civil construction, landscaping, plumbing, electrical, demolition, and tight-access projects, the DX25Z-7 offers impressive digging performance while remaining easy to transport and manoeuvre on confined job sites. Powered by a reliable Kubota diesel engine and equipped with a high-performance hydraulic system, the DX25Z-7 provides smooth, responsive operation with excellent breakout force and fuel efficiency. Its spacious operator station, ergonomic controls, and outstanding visibility ensure maximum comfort and productivity throughout the working day. The zero tail swing configuration allows operators to work confidently alongside buildings, fences, and other obstacles without compromising performance. The DX25Z-7 has an operating weight of approximately 2.7 tonnes and a maximum digging depth of 2,695 mm, making it a versatile machine for a wide range of applications. Perfect for: Tight access excavation Trenching and service installation Landscaping and site preparation Residential and commercial construction Civil works and demolition General earthmoving projects ENGINE Make DEVELON Model D18-DM01P Number of cylinders 3 Rated power, gross (hp per SAE J1995) 48.8 hp (36.4 kW) @ 2200 rpm Rated power, net (hp per SAE J1349) 47.1 hp (35.1 kW) @ 2200 rpm Max. torque, net (SAE J1995) 133.0 lbf.ft. (18.4 kgfm) @ 1600 rpm Displacement 146.0 in.3 (2.4 L) Bore and stroke 3.5 x 3.7 (90 mm x 94 mm) Starter 12 V, 3.6 hp (2.7 kW) Battery 12 V, 100 AH Alternator 12 V, 90 A Air cleaner Double elements Unit 1.3 m arm Operating weight kg 2 691 Bucket capacity (SAE heaped), standard m3 0.07 A Overall length mm 4 170 B Overall width mm 1 550 C Overall height mm 2 452 D Overall width of upperstructure mm 1 490 E Overall height of cab mm 2 452 F Ground clearance of counterweight mm 504 G Overall height of engine hood mm 1 522 H Minimum ground clearance mm 183 I Rear-end swing radius (add. CW) mm 775 (875) J Distance between tumblers mm 1 550 K Undercarriage length mm 1 975 L Undercarriage width mm 1 550 M Track gauge mm 1 250 N Track shoe width, standard mm 250 O Blade height mm 300 P Ground clearance of blade up mm 328 Q Blade depth mm 348 Unit 1.3 m arm A Max digging reach mm 4 725 A Max digging reach on ground mm 4 600 B Max digging depth mm 2 695 B Max digging depth (8 ft level) mm 2 230 C Max vertical wall digging depth mm 2 200 D Max digging height mm 4 290 E Max dumping height mm 2 975 F Min swing radius mm 2 100 Boom swing radius (left/right) mm 70 / 50 MACHINE DIMENSIONS DRIVE SYSTEM Travel speed (low high) 2.38 / 4.35 km/h Maximum traction 2.266 t Maximum gradeability 2.266 t REFILL CAPACITIES Fuel tank 30 l Cooling system (radiator capacity) 6.9 l Engine oil 5.7 l Travel device 0.6 l Hydraulic tank 27 l HYDRAULICS Main pumps 2 28.2 l/min @ 2 350 rpm Pilot pump (gear design) 20/10.5 l/min Aux. line (2 way) 48 l/min

© 2015-2026 TruckDealers.com.au. All Rights Reserved.

Product Details

Type	Dealer New
Make	Develon
Model	DX25-Z
Registration Date	8 April 2026

Further Details

configuration	Std Excav Boom
Excav Config	Std Excav Boom
Item Condition	New
Total Eng Power	48
Excav Size	1
Engine Make	Develon
Transmission	n/a
External Colour	Orange
Warranty	Enquire



© 2015-2026 TruckDealers.com.au. All Rights Reserved.