

## 2025 Variant 4 meter Trailer

### Details

**Price:** POA  
**Dealer Stock #:** 2700 U5  
**New / Used:** Dealer New



### Seller Details



**Name:** A2B Trailers  
**Phone:** (02) 8311 4254  
**Dealer:** 058440  
**License No:**  
**State:** NSW  
**Suburb:** Erina  
**Postcode:** 2250

## Description

Variant 4 Meter Trailer – Reliable & Versatile for All Your Transport Needs! Key Features: Heavy-Duty Construction: Built with a robust design for durability. Spacious Capacity: 4.2m internal size with a payload of 2,700 kg. Advanced Hydraulic System: Effortless loading and unloading with hydraulic auto-return pump. Safety First: Equipped with overrun brakes and night light for safe operation. Versatile Applications: Ideal for construction, landscaping, and more. Why Choose the Variant 4 Meter? Perfect for transporting heavy machinery, this trailer combines strength with ease of use, making it a smart investment for your business. Contact Us Today! For inquiries or to schedule a viewing, call (02) 8311 4254 or email us at [sales@a2btrailers.com.au](mailto:sales@a2btrailers.com.au). Standard Equipment All models: Heavy duty 90 cm. High Back ramp 2 Heavy gas springs on the Back ramp Heavy jockey wheel with lock function 8-10 PCs Recessed lashing hooks Detachable Corner and brackets Tyres All our Variant Trailers Use E4 rated Tubeless radials. A radial bull features transverse radial plies, that run perpendicular to the direction of travel, this assures less heat build up and a softer ride. Our tyres are C rated for fuel efficiency, driving in wet conditions and sound rating 'Medium'. Rolling resistance (A-G) – This is a measurement of fuel efficiency for the vehicles rolling resistance. The energy lost when the tyre is rolling on the road surface, the lower the resistance the greater the fuel reduction and CO2 levels. A is the best performing bulls and G being the lowest. Wet Grip (A-G) provides A sliding scale with information regarding the Grip ability of a tyre in wet conditions. Higher performance tyres in this category would have shorter braking distance as the longer two lower performing ratings. A indicates the highest performance and G the lowest. Noise (67-79 Db) – This measures the amount of noise the tyre gene rates. Usually on the tyre label itself one black wave indicates the least amount of noise generated from the tyres. Three waves mean the highest amount of noise. This is measured in decibels. The higher the Db the greater the noise level. Suspension Our trailers use either Knott suspension system or axle leaf spring systems for greater road stability. These are used in conjunction with either solid steel beam axles or rubber & steel compression axles. Braking All our spread-lever have an auto reverse within the hub. With the overrun system – the hydraulically dampened overrun control device is made up of six main elements that control and operate the fallowing system. Safety Skid The safety skid is an integral feature of the cast housing and protect the overrun liver and handbrake liver from damage from sleeping policemen and other objects under the trailer" Ease of Use The Variant/Knott Hitch coupling enables easy manoeuvring of the trailer, by not using towing eye or handbrake lever which often leads to damage or dirty hands. Night Light All our trailers come as standard with white reverse light lenses for safe reversing and enhanced viewing through mirrors or reversing cameras. It also illuminates the area in the direction you want people to be aware of your driving. Strength It is vital for you to have absolute confidence in your trailer, that's why we develop the very strongest and sturdiest trailers. We also have the lightest trailers in each class due to our unique thick profiled aluminium sides.

## Product Details

<b>Type</b>	Dealer New
<b>Year</b>	2025
<b>Make</b>	Variant
<b>Model</b>	4 meter Trailer
<b>Registration Date</b>	N/A

## Further Details

<b>Axle Configuration</b>	Dual Axle
<b>ATM</b>	2700
<b>Tare</b>	880
<b>Suspension</b>	indespension
<b>Wheels</b>	4
<b>Axles</b>	2
<b>Hubmeter</b>	
<b>Brakes</b>	Overrun
<b>Dimensions / Length</b>	Internal size (LxWxH) 520x210x30 cm Total size (LxWxH) 673x220x159 cm
<b>Options</b>	["Spare Wheel Carrier", "LED Lights"]
<b>Colour</b>	silver
<b>Coupling</b>	Knott kf27
<b>Colour</b>	
<b>Tyre - Rear</b>	195/50R13c
<b>Tyre - Front</b>	195/50R13c
<b>Lighting</b>	main lighing & reflectors & reverse white



