UBTECH Hydraulic Post Driving Silenced Hammer UBT40S Skid Steer Loader

Details

Price: \$12,500 Ex. GST

Dealer Stock #: Hydraulic Post Driving Silenced Hammer UBT40S Skid Stee

New / Used: Dealer New



Seller Details



Name: Southern Tool +

Equipment

Phone: (07) 3177 7347

State: QLD

Suburb: DARRA

Postcode: 4076

Generated: 2025-09-21 09:03 Page 1 / 3

Description

UBTECH Hydraulic Post Driving Silenced Hammer UBT40S Skid Steer Loader ATTUBT Hydraulic Hammer Suit Post Driving Bobcat Skid Steers----ONLY \$12,500.00 + GST UBTECH UBT40S Skid Steer Loader Hydraulic Post Driver. Post Driving Hammer to suit 3 to 7 Ton Skid Steer Loaders (Bobcats). ** Drives Posts 2500m to 3000mm in Overall Length (depending on the specifications of your machine performance will vary) e.g. Terex PT50 achieves 2.7m overall available height from ground to inside of post driving moil. UBTECH Hammers are manufactured in South Korea as with hammers available on the market today. PROVEN QUALITY AND VALUE FOR MONEY. 5 Years Warranty on Main Frame & 12 Months Factory Parts Warranty. *Factory warranty does not cover everyday wear parts, consumables or everyday maintenance issues. UBTECH Hammers are the heaviest in the market we have seen. When comparing weights of hammers it is important to consider whether the head bracket, hoses and moil are included! All hammers are sold WORK READY with no surprise costs when it comes to fitting your hammer to your machine, come complete with moil, hoses and head bracket installed. Hydraulic hoses supplied standard with screw-in fittings. Simply attach to the excavator and begin work with your breaker pre-gassed, flow and pressure tested, and fully adjusted to suit your machine.

Package come with UBT40S, to suit Skid steer and Track Loaders: TAKUCHI TL240, TL250 TL10 TL12. TEREX PT70, PT80, ASV PT70 PT80 PT100. BOBCAT S250 S330 S630 S650 T635 T650. MUSTANG 2076. KOMATSU SK1020. NEW HOLLAND L185. CAT 236B 242B 257B 246C 262C 272C. WACKER NEUSON 901S. CASE SR200, SR220. Gross Weight------340 kg (without Frame, Moils, Pins, Hoses). Required Oil Flow------30 to 70 L/min. Operating Pressure-----95 to 130 bar (1380 to 1885 psi). Setting Pressure------170 bar (2465 psi). Tool Shank Diameter----68 mm (2.67 inches). Impact Rate-------500 to 900 bpm. Hose Diameter-----12.7 mm (1/2 inch) All units come complete with: 1 x Mounting Bracket . 2 x Mounting Pins . 2 x Hydraulic Hoses . 1 x Tool Kit . 1 x Recharge Kit . 1 x Full Seal Kit . 1 x 100mm Post Driving Moil (80mm Internal Diameter) . 1 x Chisel Attachment . 1 x Moil Attachment

Product Details

Price \$12,500

Type Dealer New

Model UBT40S

Registration N/A

Date

Generated: 2025-09-21 09:03 Page 2 / 3



Generated: 2025-09-21 09:03 Page 3 / 3