

2025 flatbed trailer 2018P4

Details

Price: \$8,818 Inc. GST

Dealer Stock #: 2018P4

New / Used: Dealer New



Seller Details



Name: A2B Trailers

Phone: (02) 8311 4254

Dealer 058440

License No:

State: NSW

Suburb: Erina

Postcode: 2250

Description

Weights and Measures: Inside Size (LxWxH) 415x175x35 cm Total size (LxWxH) 544x180x103 cm Loading height 69 cm Total Weight 2000 kg Tare/Payload 500kg/1,500 kg Extremely lightweight, durable and safe in design. Structure: Wheel 4 PCs, 195/5013 " Axles 2 PCs, with brake Side Material Aluminum Bottom Finish, 15 mm Standard Equipment: Retractable Heavy Duty Jockey Wheel 13 or 7 pin plugs Inside lashing rings - 10 PCs. Retractable/removable sides Removable corner posts Extra strong prop stand -rear Full Marker lights and amber reflectors Optional Extras Available With This Model: Flat Tarpaulin Extra Alu-sides open up., 35 High pressure/stand, inside 145 cm High pressure/stand, inside 210 cm Net grid, 60 cm Aluminum Bottom Front Stand LED Light kit incl.control box Excludes stamp duty, rego or transport from sales warehouse to client. For more information Email or call the attached number. Why Variant.. At A2B Trailers we believe in providing customers with the highest quality and utmost safety. The features of our trailers are un-matched by competitors and truly the best in the industry. Tyres All our Variant Trailers Use E4 rated Tubeless radials. A radial bull features transverse radial plies, that run perpendicular to the direction of travel, this assures less heat build up and a softer ride. Our tyres are C rated for fuel efficiency, driving in wet conditions and sound rating ' Medium'. Rolling resistance (A-G) – This is a measurement of fuel efficiency for the vehicles rolling resistance. The energy lost when the tyre is rolling on the road surface, the lower the resistance the greater the fuel reduction and CO2 levels. A is the best performing bulls and G being the lowest. Wet Grip (A-G) provides A sliding scale with information regarding the Grip ability of a tyre in wet conditions. Higher performance tyres in this category would have shorter braking distance as the longer two lower performing ratings. A indicates the highest performance and G the lowest. Noise (67-79 Db) – This measures the amount of noise the tyre gene rates. Usually on the tyre label itself one black wave indicates the least amount of noise generated from the tyres. Three waves mean the highest amount of noise. This is measured in decibels. The higher the Db the greater the noise level. Suspension Our trailers use either Knott suspension system or axle leaf spring systems for greater road stability. These are used in conjunction with either solid steel beam axles or rubber & steel compression axles. Braking All our spread-lever have an auto reverse within the hub. With the overrun system – the hydraulically dampened overrun control device is made up of six main elements that control and operate the fallowing system. Safety Skid The safety skid is an integral feature of the cast housing and protect the overrun liver and handbrake liver from damage from sleeping policemen and other objects under the trailer" Ease of Use The Variant/Knott Hitch coupling enables easy manoeuvring of the trailer, by not using towing eye or handbrake lever which often leads to damage or dirty hands. Night Light All our trailers come as standard with white reverse light lenses for safe reversing and enhanced viewing through mirrors or reversing cameras. It also illuminates the area in the direction you want people to be aware of your driving. Strength It is vital for you to have absolute confidence in your trailer, that's why we develop the very strongest and sturdiest trailers. We also have the lightest trailers in each class due to our unique thick profiled aluminium sides. 'Danish quality and design, European style and strength – 'World class'

Product Details

Price	\$8,818
Type	Dealer New
Year	2025
Make	flatbed trailer
Model	2018P4
Registration	N/A
Date	

Further Details

Axle Configuration	Dual Axle
ATM	2000 kg
Tare	500 kg
Suspension	Independent Rubber Torsion
Wheels	4
Axles	2
Hubmeter	No
Brakes	Over Run
Dimensions / Length	544 x 180 x 103
Options	["LED Lights"]
Colour	Galvanized
Coupling	Knott
Colour	Galvanized
Tyre - Rear	195/50
Tyre - Front	195/50
Lighting	All Sides

